Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 13.06.2018 Revision: 13.06.2018 Version number 22

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MA 4520 red
- · Article number: 100000001155
- · Registration number

The ingredients of this ink meet the criteria of the Regulation 1907/2006/EC (REACH).

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Currently no such applications are identified.
- Application of the substance / the mixture $alcohol\ based\ permanent\ marking\ ink$
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

DOKUMENTAL GmbH & Co KG Woellnerstraße 26 D-67065 Ludwigshafen Phone + 49(0)621/37702 321 Fax + 49(0)621/37702 391 www.dokumental.de

· Further information obtainable from:

Technical Service, Dr. B. Polzin Tel.: +49-621-37702 322 Mobile +49-1726204412 E-Mail: bernd.polzin@dokumental.de • 1.4 Emergency telephone number: GBK Gefahrgut Büro GmbH

+49 (0) 6132 / 84463 Ingelheim, Deutschland

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Muta. 2 H341 Suspected of causing genetic defects.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Trade name: MA 4520 red

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

propan-1-ol
C.I. Basic Red 1
C.I. Solvent Orange 3
Benzenesulfonic acid, 4-C10-13-sec-alkylderivs.

· Hazard statements

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· 2.3 Other hazards

 \cdot Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 71-23-8 EINECS: 200-746-9 Reg.nr.: 01-2119486761-29	propan-1-ol Flam. Liq. 2, H225; � Eye Dam. 1, H318; � STOT SE 3, H336	50-100%
CAS: 989-38-8 EINECS: 213-584-9 Reg.nr.: 01-2120770484-49	C.I. Basic Red 1 Acute Tox. 3, H301; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1B, H317	2.5-10%
CAS: 85536-14-7 EINECS: 287-494-3 Reg.nr.: 01-2119490234-40	Benzenesulfonic acid, 4-C10-13-sec-alkylderivs. Skin Corr. 1C, H314; Acute Tox. 4, H302; Aquatic Chronic 3 H412	≤ 2.5%
CAS: 495-54-5 EINECS: 207-803-7 Reg.nr.: 01-2120754909-37	C.I. Solvent Orange 3 Muta. 2, H341; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Acute Tox. 4, H302; Skin Irrit. 2, H315	≤ 2.5%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- $\cdot \ \textbf{After eye contact:} \ \texttt{Rinse opened eye for several minutes under running water.} \ \texttt{Then consult a doctor.}$
- · After swallowing: If symptoms persist consult doctor.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Trade name: MA 4520 red

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- \cdot 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

 \cdot 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 4)

(Contd. of page 3)

Trade name: MA 4520 red

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the

Due to missing tests no recommendation to the glove material can be given for the product/ the

preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If only a short-term loading of the glove material by splashes is expected, tricoted gloves with higher wearability for the better acceptance of the users are recommended.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Nitrile rubber, NBR

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

SECTION 9: Physical and chemical properties

٠	9.1	Information	on	basic	physical	and	chemical	properties
---	-----	-------------	----	-------	----------	-----	----------	------------

· General Information

· Appearance:

Form: Fluid

Colour: According to product specification

· Odour: Product specific · Odour threshold: Not determined.

· Important information on protection of health and

environment, and on safety.

· pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 96,5-97,5 °C

· Flash point: 23 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 360 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Not determined.

· Explosion limits:

Lower 2,1 Vol %

Upper: 13,5 Vol %

· Vapour pressure at 20 °C: 19 hPa

· Density at 20 °C: $0,9 \text{ g/cm}^3$

Not determined. Relative density · Vapour density Not determined.

· Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Fully miscible.

· Viscosity:

Dynamic at 20 °C: 3.5 mPas

· Partition coefficient: n-octanol/water:

(Contd. on page 5)

Printing date 13.06.2018 Revision: 13.06.2018 Version number 22

Trade name: MA 4520 red

	(Contd. of page	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	87,1 %	
Solids content:	9,4 %	
· 9.2 Other information	The physical and chemical properties given i Section 9.1 are rough data only, which are partially derived from the component's data the mixture. These data are no binding produ specifications.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- \cdot 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 val	· LD/LC50 values relevant for classification:					
71-23-8 pro	71-23-8 propan-1-ol					
Oral	LD50	8,000 mg/kg (rat)				
Dermal	LD50	4,000 mg/kg (rab)				
Inhalative	LC50/4 h	33.8 mg/l (rat)				
989-38-8 C.	989-38-8 C.I. Basic Red 1					
Oral	LD50	250 mg/kg (rat)				
85536-14-7	85536-14-7 Benzenesulfonic acid, 4-C10-13-sec-alkylderivs.					
Oral	LD50	1,350 mg/kg (rat)				

- · Primary irritant effect:
- \cdot Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- \cdot CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity

Suspected of causing genetic defects.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:

989-38-8 C.I. Basic Red 1

EC50 / 48h | 0.16 mg/l (Daphnie) (OECD guideline 202)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

(Contd. on page 6)

Trade name: MA 4520 red

(Contd. of page 5)

- Toxic for aquatic organisms
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue					
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS				
08 01 00	wastes from MFSU and removal of paint and varnish				
08 01 13*	sludges from paint or varnish containing organic solvents or other dangerous substances				

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION	14:	Transport	informa	tio	on
DECITOR		TTUINPUT	TIII OI IIIG		

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· IMDG	PAINT (chrysoidine, xanthene dye, red), MARINE
	POLLUTANT
· IATA	PAINT

- · 14.3 Transport hazard class(es)
- · ADR





· Class 3 (F1) Flammable liquids.

· Label

· IMDG





· Class 3 Flammable liquids.

Label

· IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group · ADR, IMDG, IATA III · 14.5 Environmental hazards: Pro

14.5 Environmental hazards:

 Product contains environmentally hazardous substances: xanthene dye, red

 Marine pollutant:

 Yes
 Symbol (fish and tree)

 Special marking (ADR):
 Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 30
 EMS Number: F-E,S-E
 Stowage Category A

(Contd. on page 7)

Trade name: MA 4520 red

(Contd. of page 6) · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: Limited quantities (LQ) 5L · Excepted quantities (EO) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · Transport category .3 · Tunnel restriction code D/E· IMDG Limited quantities (LQ) 5L · Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml $\,$ · UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

Class	Share in %
NK	50-100

- · Waterhazard class: Water hazard class 3 (Self-assessment): extremely hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

PBT: Persistent, Bioaccumulative and Toxic

VPVB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1C: Skin corrosion/irritation - Category 1C

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

Skin Sens. 1B: Skin sensitisation - Category 1B Muta. 2: Germ cell mutagenicity - Category 2

(Contd. on page 8)

Printing date 13.06.2018 Revision: 13.06.2018 Version number 22

Trade name: MA 4520 red

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.